

Special-purpose, single-phase unit for painters and facade cleaning contractors. Accommodated in a sturdy tubular steel cage.

**Standard accessories:**

- Trigger gun Easy-press trigger gun
- Trigger gun with Softgrip insert
- High-pressure hose 10 m
- Spray lance 600 mm
- Triple nozzle (0°/25°/40°)  
Touchless
- Anti-twist system
- Pressure cut-off



**Order no.: 1.284-103.0**

**Technical data**

Type of current Ph/V/Hz	1/230/50
Flow rate (l/min)	4-11.6
Operating pressure (bar/psi)	10-80/145-1160
Max. pressure (bar)	-
Max. feed temperature (°C)	up to 60
Power rating (kW)	2,2
Weight (kg)	29
Dimensions (L x W x H) (mm)	500x310x350

## Details

### Description

Portable cold water high-pressure cleaner developed to meet the special requirements of painters and facade cleaning contractors. This handy single-phase unit is protected from mechanical damage by a tubular steel cage and is particularly suitable for cleaning operations on scaffolding. It has a short spray lance (540 mm) to ensure that a sufficient spraying distance can be maintained when working on scaffolding. The lance is pivot mounted in the trigger gun so that it can be rotated to reach awkward corners and surfaces with difficulty. The new triple nozzle (standard equipment) enables the user to quickly select the type of jet that best suits the cleaning job, i.e. either a high-pressure pencil jet, 25° high-pressure fan jet or 40° low-pressure fan jet. The familiar Dirt Blaster (rotary nozzle), which is available to exactly match every Kärcher high-pressure cleaner, can be used in the case of more stubborn dirt and stains, such as lime efflorescence. A particularly robust, high quality hose is used. The unit is mounted on rubber feet to prevent vibrations being transmitted to the scaffolding and makes sure the machine does not creep. The motor and electrical equipment are installed in a splash-proof housing. The three-piston axial pump with stainless steel pistons and brass cylinder head guarantees a long service life and exceptional durability. The pressure switch control turns the motor off automatically as soon as water feed is interrupted at the trigger gun. Energy is saved in this way. Transportation is simple because the unit weighs only 25 kg. It will fit in every station wagon and can also be carried by hand. Finding a suitable power supply is not a problem thanks to the unit's single-phase motor (connected load 3.3 kW). It goes without saying that the HD 600 can also be used for all other cleaning jobs in the workshop or vehicle fleet.

---